


	Date:
	Client:
	Project:



5475S-081D

¾" thermostatic mixer.

5475S-081DUP = Thermostatic mixer 5400N.


5475S-081DAP = Handle NR51, handle NR52, handle NR64G, hand shower and hand shower holder with non-return valve 070S, hose 1500 mm, 115 mm double head shower 080D, five-hole plate 60 x 387 mm 5005B.

Flow


	Bar:	1.0	2.0	3.0	4.0	5.0
080D ¹⁾	(l/min)	14.4	20.4	25.0	28.9	32.3
070S ²⁾	(l/min)	6.9	9.8	12.0	13.9	15.5

¹⁾ USA: Flow restricted to 1.8 gpm (7.0 l/min)


²⁾ USA: Flow restricted to 2.0 gpm (7.6 l/min)

**Available in colors**


Color 02, Grey	Color 21, Carmine red
Color 04, Light blue	Color 25, Pink
Color 05, Orange	Color 27, Matt black
Color 06, Light green	Color 28, Matt white
Color 08, Yellow	Color 40, Brushed stainless steel
Color 09, Dark grey	Color 60, Black
Color 12, Mocca	Color 61, Brushed black
Color 14, Bright red	Color 62, Deep black
Color 15, Dark blue	Color 63, Copper
Color 16, Polished chrome	Color 64, Brushed Copper
Color 17, Gloss black	Color 65, Gold
Color 18, White	Color 68, Silver
Color 19, Natural brass	Color 70, Brushed Gold
Color 20, Brushed chrome	

**001**


60 mm circular flange.
Hole Ø30 mm.

**070S**

Hand shower, hand shower holder and hose with non-return valve.


**080D**

130 mm double head shower.
60 mm cover flange included.




**5005B**


Five-hole plate (for 5400 w. T8), Ø39, Ø39, Ø39, Ø30, Ø33 mm, 387x60 mm.

**5400N**

Thermostatic mixer with diverter and fixed outlet socket and one separate outlet socket, 200M.
 $\frac{3}{4}$ " connection to copper, steel, iron or pex pipe work.



**NR51**

On/off handle for series 5000.



**NR52**

Thermostatic handle for series 5000.

**NR64G**

Diverter handle for 5400/5600.

With peg in the same colour as handle (Standard).

